

Dome Camera DBD 154060/1540600

Description

CCD Colour Dome Camera (Day/Night) in vandal proof housing for buses and railway.
Indoor installation through BNC/AMP connector

Item number

DBD 154060 VZM200210
DBD 1540600 VZM200215

Main features

- Horizontal Resolution: 560TVL / 600 TVL
- Lens: f=3.6 mm (154060), f=2.9 mm (1540600)
- Electronic Shutter Control (ESC)
- Fast Internal Synchronization
- Easy Installation



Sensor	1/3" Sony Super HHD 2 Chip
System	PAL, 625 lines, 50 half frames/s 50 Hz (vertical) / 15.625 (horizontal)
Backlight compensation	automatic
Synchronization	Internal
Sensitivity	0.1 Lux
Horizontal resolution	560 TVL (Day) / 600 TVL (Night)
Pixels	approx. 440 000
Signal-to-Noise Ratio	> 48dB (AGC off)
Linear shutter (ESC)	1/60 to 1/1000 000 sec., depending on lighting conditions
Video output	1 Vss, BAS, 75 Ohm
Gamma correction	approx. 0.45
Lens	3.6 mm, 52° V, 62° H (154060) 2.9 mm, 63° V, 84° H (1540600)
Operating voltage	12 VDC
Installation type	indoor
Power consumption	max. 2.5 W
External connections	Video (BNC), 12 VDC-In
Environment	-10°C to +60°C
Dimensions	79 x 55 mm (W x H)
Housing	Vandal proof aluminum, IK10
Weight	approx. 300 g
Conformity & Certification	E13, EN50155

Information refers to the current state and may be subject to unannounced changes.

2/1/2021