

HydralP MR4410

Description

Digital 4-channel hybrid recorder of the HydralP series for the recording of analog and digital camera signals. Specially designed and certified for mobile use in road and railway vehicles.

Article number

MR4410 VPV300057
MR4410 4G WLAN VPV300083

Main features

- Complete integration into vehicle systems
- Fast & easy installation
- Compliant to IBIS VDV300 and IBIS VDV301 (IBIS over IP)
- Compliant to ITxPT
- Robust housing, fanless and no ventilation slots
- Electronic key for storage media removal (HydralP SmartKey)
- Data security by multilayer security concept (HydralP SmartLock)
- GPS module included (GNSS GPS-NAVSTAR)
- Recording of additional data (audio, event data, IBIS...)
- Optional transmission module (LTE/4G/3G/WLAN) available
- Expendable with automatic people counting and fleet management system
- Low cost beginner system



System	<p>Multi processor system with automatic self-monitoring (temperature, error states) UNIX operating system Internal real time clock (RTC) The power supply of the storage media is buffered with super caps FW-Updates and configuration by direct connection or USB stick Integrated web interface (HydralP ServiceTool) for configuration, system diagnostic and data download Plugin concept for fast implementation of special functions</p>
Recording	<p>Flexible definition of ring and alarm recording Automatic deletion of data according to FIFO principle Recording time of up to 30 days (depending on the individual settings of the system and capacity of the storage media)</p> <p>Analog Video: Up to 100fps (4 CIF) Supported resolutions: CIF (352 x 288), 2CIF (720 x 288), 4CIF (704 x 576) Video compression: H.264</p> <p>Digital Video (IP): Video compression: H.264</p> <p>Additional data: Audio, IBIS VDV300, IBIS VDV301 (IBIS over IP), event data (System state, Diagnostic data.), GPS data, CAN-FMS, acceleration data of internal acceleration sensor</p>
Interlocking System & Data Security	<p>Electromechanical locking of storage media for protection against unauthorised or premature removal of the storage media. Removal of the storage media by an electronic key (HydralP SmartKey). Removal of the storage media is not possible before writing- and reading-processes have stopped. Loss of data or damage of storage media in cause of premature removal is avoided. Removal of the storage media from currentless system possible. To analyse the recorded video data, the analysis station USB-TTU and the DResearch analysis software application ImageFinder NX is required. All data are recorded in special data format and are not readable in any other system. For giveaway of the encrypted data a special player software ImageFinder NX Player is available.</p>

	Possibility of four-eyes principle for inspection of video data with ImageFinder NX (according to data security standards).
Video output	1 x PAL (720 x 576 px) Single and multiview of all camera signals. Freely configurable manual, automatic or event controlled screen switching
Interfaces	4 x Video In (CVBS, BNC) PAL 1 x Video Out (CVBS, BNC) PAL 1 x USB 2.0 service interface 1 x Ethernet (100 Mbit/s, M12 D-coded) 1 x GPS NAVSTAR (FAKRA type C, blue) Phantom power 3,6 VDC 4 x color LED for signalization of system states 2 x Audio (5kOhm, max 2Vpp) 9 x Digital In (GPI) (2x with internal switching voltage) 2 x Digital Out (GPO) (changeover (relay), contacts: max. 60 VDC, 125 VAC, 500 mA) 1 x Stabilized power supply for external devices (12 VDC / 2 A) 1 x IBIS VDV300 1 x CAN-FMS 1 x USB 2.0 1 x Ignition signal: (low: 0–3 VDC, high: 6–34 VDC) 1 x Interface for external devices MR4410 4G WLAN: 1 x LTE/4G/3G (FAKRA type D, bordeaux) 1 x WLAN (FAKRA type I, beige)
Integration	Compliant to VDV300 IBIS, IBIS VDV301 (IBIS-IP) Compliant to ITxPT Automatic answers to IBIS state checks Remote control by network API Control by General Purpose Input (GPI) Signalling of system states by General Purpose Output (GPO) Integration into DResearch fleet management system
Power Supply	System power: 24 VDC (9 ... 32 VDC) Minimal power consumption (protection of the vehicle battery) Operational modes: SleepMode < 1 W, StandbyMode < 5 W, Recording Mode max. 12 W, with external devices max. 40 W
Environment	Operating temperature: -25°C ... +70°C EN 50155 Class T3 Storage temperature: -40°C ... +85°C Humidity: 95 % (not condensing), Active temperature management
Housing	Robust aluminum housing with cooling profile for passive cooling Fanless, no ventilation slots Protection class: IP42 integrated DIN rail and screw channel Easy and fast installation with DResearch mounting panel Dimensions (W x H x D): 100 x 84 x 208 mm Weight: approx. 1200 g (without storage media), approx. 1400 g (with storage media)
Conformities & Certification	RoHS, REACH, VDE, UN ECE R10 (E1), UN ECE R118, EN 50155, EN 61373, EN 50121-3-2, EN 50155, EN 45545-2, IEC 60068-2, EN 55022 (CE), EN 55024 (CE)

Information refers to the current states and may be subject to unannounced changes.

05.08.2022